

(12) UK Patent Application (19) GB (11) 2 314 809 (13) A

(43) Date of A Publication 14.01.1998

(21) Application No 9713467.0

(22) Date of Filing 25.06.1997

(30) Priority Data

| | | |
|---------------|-----------------|---------|
| (31) 08165009 | (32) 25.06.1996 | (33) JP |
| 08356296 | 25.12.1996 | |
| 08358766 | 27.12.1996 | |
| 09132919 | 07.05.1997 | |

(51) INT CL⁶
B41J 2/175

(52) UK CL (Edition P)
B6F FLR

(56) Documents Cited
EP 0699533 A2

(58) Field of Search
UK CL (Edition O) B6F FLR
INT CL⁶ B41J 2/175

(71) Applicant(s)
Seiko Epson Corporation

(Incorporated in Japan)

4-1 Nishi-shinjuku 2-chome, Shinjuku-ku, Tokyo,
Japan

Yoshie Kumagai
Takao Kobayashi
Hisashi Koike

(72) Inventor(s)
Kazumichi Shimada
Hideki Oikawa
Hisashi Miyazawa

(74) Agent and/or Address for Service
J Miller & Co
34 Bedford Row, Holborn, LONDON, WC1R 4JH,
United Kingdom

(54) An ink supply port arrangement for a multi-colour ink cartridge

(57) An ink cartridge 1 has a plurality of ink chambers 2a-2f wherein ink supply ports 4a-4f associated with the chambers are arranged in two linear arrays, such that the size of the cartridge can be reduced, and easy loading of the cartridge is ensured. The ink supply ports may be arranged in a zig-zag, offset manner to allow for a further reduction in the size of the chambers and cartridge. At least one reinforcing rib (15, Fig. 5(a)) is provided on the outside of the cartridge, to ensure the strength and rigidity of the cartridge. Circuitous grooves (35a-35f, Fig. 8(b)) are formed in the surface of a cover member (30) so that the grooves (35a-35c) communicating with ink chambers (12a-12c, Fig. 8(a)) having smaller volumes are longer than grooves (35d-35f) communicating with chambers (12d-12f) having larger volumes, thus insuring uniform viscosities of all of the inks.

FIG.1 (a)





FIG.1 (b)



GB 2 314 809 A

(12) UK Patent Application (19) GB (11) 2 315 045 (13) A

(43) Date of A Publication 21.01.1998

(21) Application No 9714178.2

(22) Date of Filing 04.07.1997

(30) Priority Data

| | | |
|---------------|-----------------|---------|
| (31) 08195626 | (32) 05.07.1996 | (33) JP |
| 08233588 | 14.08.1996 | |
| 09158009 | 30.05.1997 | |

(51) INT CL⁶
B41J 2/175

(52) UK CL (Edition P)
B6F FLR

(56) Documents Cited
None

(58) Field of Search
UK CL (Edition O) B6F FLR
INT CL⁶ B41J 2/175

(71) Applicant(s)
Seiko Epson Corporation

(Incorporated in Japan)

4-1 Nishi-shinjuku 2-chome, Shinjuku-ku, Tokyo,
Japan

(74) Agent and/or Address for Service

J Miller & Co
34 Bedford Row, Holborn, LONDON, WC1R 4JH,
United Kingdom

(72) Inventor(s)

Hisashi Miyazawa
Takao Kobayashi
Hisashi Koike
Hitoshi Igarashi
Masanori Yoshida

(54) Reinforced ridged cover for ink cartridge and cartridge loading mechanism

(57) An air impermeable but soft polypropylene ink cartridge 1 has reinforcing ridges 6 projected from corner portions of peripheral walls 2,3 and a thick-walled opening end edge 4. A cover 20 is sealed to the cartridge by welding and has longitudinal ridges 21 formed on an inner surface thereof, and shape retaining ridges (23, Fig. 3(a)) which project integrally from an outer surface of the ridges 21 so as to engage the body walls, so that deformation of the cartridge is suppressed during welding - any burrs thus formed are collected in a groove 25 of the cover. A cartridge (120, Fig. 12(a)-(d)) may be loaded onto a carriage without breaking an ink supply needle (119) by engaging a recess 15 in the lower surface of the cartridge with a support rod (117) of a lifter (115), and closing a pivotable carriage cover body (110) while guiding the lifter with a guide groove (106) parallel to the axial centre of the needle.

FIG. 1




FIG. 6




FIG. 1




FIG. 2(a)




FIG. 2(b)




FIG. 3(a)





FIG. 3(b)







FIG. 6




FIG. 7




FIG. 9(a)




FIG. 9(b)




FIG. 11




FIG. 12(a)




FIG. 12(c)




FIG. 12(b)




FIG. 12(d)




FIG. 13




FIG. 14

